

XBO 3000 W/DHP OFR

XBO for BARCO Projectors




Areas of application

- Digital Cinema Projection

Product features and benefits

- High luminance for brighter screen illumination
- A lifetime of consistent performances with constant 6000 K color temperature
- Continuous spectrum in the visible range
- High arc stability
- High arc stability
- Dimmable over a wide range
- Hot restart



Technical data

General Product Information

Product number (Americas)	69480
Product name (Americas)	XBO 3000W/DHP 1/CS 1/SKU
Global order reference	XBO 3000 W/DHP OFR


Electrical Data

Nominal wattage	3000 W
Nominal voltage	29 V
Nominal current	105 A
Current control range	77...113 A
Type of current	DC

Photometric Data

Nominal luminous flux	135000 lm
Light center length (LCL)	123.0 mm

Physical Attributes & Dimensions



Electrode gap (cold)	4.5 mm
Base (anode)	SFaX27-14x80
Base (cathode)	SFc27-16/55
Diameter	55.0 mm
Diameter (in)	2.165 in
Diameter	55.0 mm
Length	345.0 mm
Length with base excl. base pins/connection	295.00 mm
Cable/wire length, input side	130 mm
Connector: presence	Yes

Product datasheet

Product weight	581.00 g
----------------	----------

Operating Conditions

Burning position	s15/p15 ¹⁾
Cooling	Forced
Max. permitted ambient temp. pinch point	230 °C

¹⁾ For vertical burning position: anode (+) on top

Lifetime Data

Nominal lifetime	1500 hr
Warranty hours	1500 hrs
Service warranty lifetime	1900 hr

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4052899195783 4052899468191 4008321330048 4062172030410 4052899096073 4052899287785
Declaration no. in SCIP database	34a49bce-cf7a-477b-8d7b-991718631ed4 a303e60b-72e8-4104-9c0c-1f16adeed959 2c70619c-7452-40e1-9f11-72c36a77558d
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Product datasheet

Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172030410	XBO 3000 W/DHP OFR	Shipping carton box 1	500 mm x 204 mm x 204 mm	20.81 dm ³	1302.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.