

XBO 1600 W/DHP OFR

XBO for BARCO Projectors




Areas of application

- Digital Cinema Projection

Product features and benefits

- High luminance for brighter screen illumination
- A lifetime of consistent performances with constant 6000 K color temperature
- Continuous spectrum in the visible range
- High arc stability
- High arc stability
- Dimmable over a wide range
- Hot restart



Technical data

General Product Information

Product number (Americas)	69840
Product name (Americas)	XBO 1600W/DHP 1/CS 1/SKU
Global order reference	XBO 1600 W/DHP OFR


Electrical Data

Nominal wattage	1600 W
Nominal voltage	21 V
Nominal current	78 A
Current control range	57...86 A
Type of current	DC

Photometric Data

Light center length (LCL)	123.0 mm
---------------------------	----------

Physical Attributes & Dimensions



Electrode gap (cold)	3.5 mm
Base (anode)	SFaX30-14
Base (cathode)	SFc30-16
Diameter	46.5 mm
Diameter	46.5 mm
Length	345.0 mm
Length with base excl. base pins/connection	295.00 mm
Cable/wire length, input side	130 mm
Connector: presence	Yes
Product weight	485.00 g

Operating Conditions

Burning position	s15/p15 ¹⁾
Cooling	Forced
Max. permitted ambient temp. pinch point	230 °C

¹⁾ For vertical burning position: anode (+) on top

Lifetime Data

Nominal lifetime	3000 hr
Warranty hours	3000 hrs
Service warranty lifetime	3800 hr

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4052899254831 4062172030465
Declaration no. in SCIP database	ddc0ca29-d545-4244-bd3d-01657e49e316
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Product datasheet

Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172030465	XBO 1600 W/DHP OFR	Shipping carton box 1	500 mm x 204 mm x 204 mm	20.81 dm ³	1281.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.